



MODEL NO.	DC-087-1.65
SCHEMATIC	
CENTER PIN	ø1.65mm

*** MATERIAL**

- TERMINAL 1 :BRASS
- TERMINAL 2 :PHOSPHOR BRONZE
- TERMINAL 3 :BRASS
- HOUSING :PA66

SPECIFICATION

- Rating : DC 16V 2.5A
- Contact resistance : ≤ 50mΩ
- Insulation resistance : ≥ 100MΩ
- Withstand voltage : 500VAC
- Insertion and extraction force : 3-30N
- life test : 5,000 cycles

东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	08/12/14			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK
Jacky Chen	08/12/14			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-087-1.65
Tony Kao	08/12/14	1 : 1		
		SHEET NO.	PART NO.	DC-087-1.65
		1 of 1		

1	新增SPEC	Jack	081214
ITEM NO.	DESCRIPTION	DRAWN	DATE