



- 1.自动复位开关型号 BIASED SWITCH MODEL NO.:LXW-3-6A-J5-2
- 2.快插端子 QUICK CONNECTOR TYPE
单刀双掷 SINGLE POLE DOUBLE THROW
- 3.额定值 RATING: 16A 250VAC μT125 (KC)
16A 125/250VAC μT125 (UL;ENEC17;NEMKO;CQC)
10A 250VAC μT85 (ENEC17;NEMKO;CQC)
6A 125VAC 3A 250VAC μT85 (ENEC17;NEMKO ;CQC)
- 4.接触电阻 CONTACT RESISTANCE: <50mΩ (INITIAL)
- 5.绝缘电阻 INSULATION RESISTANCE: ≥100MΩ(DC500V/1MIN)
- 6.介电强度 DIELECTRIC STRENGTH: 1500V /5mA /1MIN
- 7.机械寿命 MECHANICAL LIFE: >50000 CYCLES
- 8.电气寿命 ELECTRICAL LIFE: >10000 CYCLES
- 9.操作力 OPERATION FORCE:150~250gf
- 10.所有部件均使用环保材料 ALL MATERIALS ARE RoHS COMPLIANT

 东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S 

UNITS MM

DRAWN BY: Ming Ming Zou	DATE 10/31/13	MAT'L	TITLE SWITCH
CHECKED BY: Ning Ning Su	DATE 10/31/13	FINISH	MODLE MICRO SWITCH
APPROVED BY: Jia Xiang	DATE 10/31/13	SCALE 1:1	DWG NO. GD-LXW-3-6A-J5-2
SHEET NO. 1 of 1		PART NO.	SIZE A4 VER R

ITEM NO.	DESCRIPTION	DRAWN	DATE