



X(mm)
2mm
3mm
4mm
5mm
6mm
7mm
8mm
9mm

SPECIFICATIONS

Rating	0.3A 50V DC
FUNCTION	1P2T
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	200gf ± 80gf
Operating Life	10,000 cycle

NO.	PARTS	MATERIALS	QTY	FINISH
5	CONTACT CLIP	PBS STRIP	1	Ag PLATED
4	TERMINAL	BRASS	3	Ag PLATED
3	BASE	PHENOLIC RESIN	1	NATURAL
2	FRAME	STEEL STRIP	1	Ni PLATED
1	KNOB	POM	1	BLACK

東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2
Above 5 - 15 ±0.3
Above 15 - 30 ±0.4
Above 30 - 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Ming Ming Zou	11/19/14		MODLE	SLIDE SWITCH
CHECKED BY:	DATE	FINISH	SCALE	1:1
Jing Ning Su	11/19/14		DWG NO.	GD-SS-12E88-3P-E
APPROVED BY:	DATE	SHEET NO.	PART NO.	
Jia Xiang	11/19/14	1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新編SPEC	Jack	11/19/14
1	新編尺寸	Jack	06/16/14

SIZE
A4
VER
R2