

产品型号		GD-TX90U-M/-F (UL认证)	
额定电流	45A	瞬间电流	90A
接触电阻	0.4mΩ	额定电压	DC500V
金属材质	铜镀金	绝缘材质	PA
工作温度	-20°C to 120°C	阻燃等级	UL94 V0
推荐线规	10AWG	推荐使用次数	100tims

4	更新材質	Jack	050420
3	更新尺寸	Jack	121119
2	更新尺寸標示位置	Jack	082719
1	更新尺寸	Jack	080519
ITEM NO.	DESCRIPTION	DRAWN	DATE




东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Ming Ming Zou	6/8/23
CHECKED BY:	DATE
Ning Ning Su	6/8/23
APPROVED BY:	DATE
Jia Xiang	6/8/23

MAT'L	TITLE	JACK
FINISH	MODLE	GD-TX connector
SCALE	DWG NO.	GD-TX-90WT-M-2+2
SHEET NO.	PART NO.	
1 of 1		

SIZE
A4
VER
R4