



产品型号 Item No.		接触电阻 CR	主铜件 ≤ 0.4 mΩ 信号针 ≤ 2 mΩ
颜色 COLOR	3	额定电压	< DC 50V
金属材质 Metal Material	铜镀金 Brass Gold Plated	额定电流 RC	60A
绝缘材质 Plastic Material	PA6 GF25 V0	瞬时电流 MC	120A
阻燃等级 FR LEVEL	UL94 V0	推荐使用次数 USE TIMES	1000 TIMES
推荐应用 Recommend USE	电池 BATTERY	推荐线规 Cable SPEC.	10AWG,
温升(接线 10AWG) TEMPERATURE RISE	60A 80°C (30min) 120A 85°C (1min)	温升(接线 12AWG) TEMPERATURE RISE	/
安规认证 CERTIFICATION	CE/UL	插拔力 Insertion Force	40N-65N 与 AS120-F 互配拔出力
焊脚高度 WELD METAL	/	工作温度 TEMPERATURE	-20°C to 120°C



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle ± 0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Ming Ming Zou
DATE: 6/8/23

CHECKED BY: Ning Ning Su
DATE: 6/8/23

APPROVED BY: Jia Xiang
DATE: 6/8/23

MAT'L	TITLE	JACK
FINISH	MODLE	GD-TX connector
SCALE	DWG NO.	GD-TX-90WT-S4-G
SHEET NO.	PART NO.	
1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	更新材質	Jack	050420
3	更新尺寸	Jack	121119
2	更新尺寸標示位置	Jack	082719
1	更新尺寸	Jack	080519