


主要技术特性要求:

1. 额定负荷: 250V AC 10A
2. 绝缘电阻: $\geq 100M\Omega$
3. 耐压: AC2000V (50Hz) 1min
4. 插拔力: 20~60N

9	321008	地线端子	磷铜T=0.6	1	镀锡	
8	321007	L端子	磷铜T=0.6	1	镀锡	
7	321006	N端子	磷铜T=0.6	1	镀锡	
6	310700	底座	PA6-GF	1	黑色	
5	310701	隔板	PA6-GF	1	黑色	
4	310702	二孔安全门	PA6-GF	1	黑色	
3	310703	三孔安全门	PA6-GF	1	黑色	
2	321009	弹簧	钢丝 $\phi 0.3$	1	清洗	
1	310699	面板	PA6-GF	1	黑色	
序号	零件料号	名称	材料	数量	镀层/颜色	备注

 东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ± 0.2 , Above 5 ~ 15 ± 0.3 , Above 15 ~ 30 ± 0.4 , Above 30 ~ 50 ± 0.5 , Angle $\pm 0.3^\circ$

3RD. ANGEL'S  UNITS MM

DRAWN BY: Ming Ming Zou DATE: 10/31/13
CHECKED BY: Ning Ning Su DATE: 10/31/13
APPROVED BY: Jia Xiang DATE: 10/31/13

MAT'L	TITLE	SWITCH
FINISH	MODLE	AC POWER SOCKET
SCALE	DWG NO.	GD-AC-302
SHEET NO.	PART NO.	

SIZE: A4, VER: R

ITEM NO.	DESCRIPTION	DRAWN	DATE