

SPECIFICATION

A: MATERIAL:

- 1. HOUSING & COVER: PC(BLACK), UL 94V-0
- 2. HANDLE: PC(RED), UL 94V-0
- 3. DOOR: IRON ALLOY, NICKEL PLATED
- 4. TERMINAL: COPPER ALLOY, TIN PLATED
- 5. SPRING: IRON ALLOY, NATURE

B: CHARACTERISTICS:


- 1. RATING: 10A 250V~ TUV,CCC
15A 250V~ UL
- 2. INSULATION RESISTANCE: 100MΩ MIN, AT 500V DC
- 3. ELECTRIC STRENGTH: AC 2000V FOR ONE MINUTE
- 4. PREVENT SHEDDING FORCE: 10KG MIN.

C: APPROVALS:

UL, CUL, TUV & CCC

 **東莞市高迪電子有限公司**
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S  UNITS MM

DRAWN BY: DATE
Ming Ming Zou 10/31/13

CHECKED BY: DATE
Ning Ning Su 10/31/13

APPROVED BY: DATE
Jia Xiang 10/31/13

MAT'L		TITLE	SWITCH
FINISH		MODLE	AC POWER SOCKET
SCALE	1:1	DWG NO.	GD-BT-13-1A
SHEET NO.	1 of 1	PART NO.	

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE
A4
VER
R