


产品类型特性

- 1. AC插座 材质
- 2. 塑胶件 PA66
- 3. 插销黄铜镀镍
- 4. 端子黄铜镀锡
- 1. 使用温度范围:  $-10^{\circ}\text{C} \pm 70^{\circ}\text{C}$
- 2. 额定值: 10A/15A AC 125V 250AC
- 3. 绝缘电阻:  $100\text{M}\Omega$
- 4. 耐电压: 2500V AC
- 5. 接触电阻:  $30\text{M}\Omega$
- 6. 寿命: 5000次
- 结构特性 插拔力:  $13.6\text{N} \sim 68\text{N}$
- 端子强度: 60N
- 盐雾测试:  $35 \pm 2^{\circ}\text{C}$  24/h
- 耐环境性能 耐寒性能  $-20 \pm 2^{\circ}\text{C}$  96/h
- 耐热性能  $100 \pm 2^{\circ}\text{C}$  96/h
- 耐湿性能  $40 \pm 2^{\circ}\text{C}$  相对湿度90~95% 96/h

 东莞市高迪电子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5  $\pm 0.2$ , Above 5 ~ 15  $\pm 0.3$ , Above 15 ~ 30  $\pm 0.4$ , Above 30 ~ 50  $\pm 0.5$ , Angle  $\pm 0.3^{\circ}$

3RD. ANGEL'S  UNITS MM

DRAWN BY: Ming Ming Zou DATE: 10/31/13  
CHECKED BY: Ning Ning Su DATE: 10/31/13  
APPROVED BY: Jia Xiang DATE: 10/31/13

MAT'L		TITLE	SWITCH
FINISH		MODLE	AC POWER SOCKET
SCALE	1:1	DWG NO.	GD-BT-14-2A-P13
SHEET NO.	1 of 1	PART NO.	

SIZE: A4  
VER: R

ITEM NO.	DESCRIPTION	DRAWN	DATE