

产品类型特性

1. AC插座 材质
  2. 塑胶件 PA66
  3. 插销黄铜镀镍
  4. 端子黄铜镀锡
  1. 使用温度范围:  $-10^{\circ}\text{C} \pm 70^{\circ}\text{C}$
  2. 额定值: 10A/15A AC 125V 250AC
  3. 绝缘电阻:  $100\text{M}\Omega$
  4. 耐电压: 2500V AC
  5. 接触电阻:  $30\text{M}\Omega$
  6. 寿命: 5000次
- 结构特性 插拔力:  $13.6\text{N} \sim 68\text{N}$   
 端子强度: 60N  
 盐雾测试:  $35 \pm 2^{\circ}\text{C}$  24/h  
 耐环境性能 耐寒性能  $-20 \pm 2^{\circ}\text{C}$  96/h  
 耐热性能  $100 \pm 2^{\circ}\text{C}$  96/h  
 耐湿性能  $40 \pm 2^{\circ}\text{C}$  相对湿度90~95% 96/h




東莞市高迪電子有限公司  
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS  
 OTHERWISE STATED :

Up to 5  $\pm 0.2$   
 Above 5 ~ 15  $\pm 0.3$   
 Above 15 ~ 30  $\pm 0.4$   
 Above 30 ~ 50  $\pm 0.5$   
 Angle  $\pm 0.3^{\circ}$

3RD.  
 ANGEL'S



UNITS

MM

DRAWN BY: DATE  
 Ming Ming Zou 10/31/13

CHECKED BY: DATE  
 Ning Ning Su 10/31/13

APPROVED BY: DATE  
 Jia Xiang 10/31/13

MAT'L		TITLE	SWITCH
FINISH		MODLE	AC POWER SOCKET
SCALE	1:1	DWG NO.	GD-DB-14-1C
SHEET NO.	1 of 1	PART NO.	
			SIZE A4
			VER R

ITEM NO.	DESCRIPTION	DRAWN	DATE