

产品类型特性

1. AC插座 材质

2. 塑胶件 PA66

3. 插销 黄铜镀镍

4. 端子 黄铜镀锡

1. 使用温度范围:  $-10^{\circ}\text{C} \pm 70^{\circ}\text{C}$

2. 额定值: 2.5A/5A/7A AC 125V 250V AC

3. 绝缘电阻:  $100\text{M}\Omega$

4. 耐电压: 2500V AC

5. 接触电阻:  $30\text{M}\Omega$

6. 寿命: 10000次

结构特性 插拔力:  $13.6\text{N} \sim 68\text{N}$

端子强度: 60N

盐雾测试:  $35 \pm 2^{\circ}\text{C}$  24/h

耐环境性能 耐寒性能  $-20 \pm 2^{\circ}\text{C}$  96/h

耐热性能  $100 \pm 2^{\circ}\text{C}$  96/h

耐湿性能  $40 \pm 2^{\circ}\text{C}$  相对湿度90~95% 96/h




東莞市高迪電子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS  
OTHERWISE STATED:

Up to 5  $\pm 0.2$   
Above 5 ~ 15  $\pm 0.3$   
Above 15 ~ 30  $\pm 0.4$   
Above 30 ~ 50  $\pm 0.5$   
Angle  $\pm 0.3^{\circ}$

3RD.  
ANGEL'S



UNITS

MM

DRAWN BY: DATE

Ming Ming Zou 10/31/13

CHECKED BY: DATE

Ning Ning Su 10/31/13

APPROVED BY: DATE

Jia Xiang 10/31/13

MAT'L

FINISH

SCALE

SHEET NO.

TITLE

MODLE

DWG NO.

PART NO.

SWITCH

AC POWER SOCKET

GD-DB-5ES

SIZE

A4

VER

R

ITEM NO.	DESCRIPTION	DRAWN	DATE