

产品类型特性

1. AC插座 材质
  2. 塑胶件 PA66
  3. 插销 黄铜镀镍
  4. 端子 黄铜镀锡
  1. 使用温度范围:  $-10^{\circ}\text{C} \pm 70^{\circ}\text{C}$
  2. 额定值: 2.5A/5A/7A AC 125V 250V AC
  3. 绝缘电阻:  $100\text{M}\Omega$
  4. 耐电压: 2500V AC
  5. 接触电阻:  $30\text{M}\Omega$
  6. 寿命: 10000次
- 结构特性 插拔力: 13.6N~68N  
 端子强度: 60N  
 盐雾测试:  $35 \pm 2^{\circ}\text{C}$  24/h  
 耐环境性能 耐寒性能  $-20 \pm 2^{\circ}\text{C}$  96/h  
 耐热性能  $100 \pm 2^{\circ}\text{C}$  96/h  
 耐湿性能  $40 \pm 2^{\circ}\text{C}$  相对湿度90~95% 96/h




東莞市高迪電子有限公司  
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Ming Ming Zou	10/31/13
CHECKED BY:	DATE
Ning Ning Su	10/31/13
APPROVED BY:	DATE
Jia Xiang	10/31/13

MAT'L	TITLE	SWITCH
FINISH	MODLE	AC POWER SOCKET
SCALE	DWG NO.	GD-DB-7GP9
SHEET NO.	PART NO.	

SIZE  
 A4  
 VER  
 R

ITEM NO.	DESCRIPTION	DRAWN	DATE