

**PANEL CUT-OUT**

产品类型特性

- 1. AC插座 材质
- 2. 塑胶件 PA66
- 3. 插销 黄铜镀镍
- 4. 端子 黄铜镀锡
- 1. 使用温度范围:  $-10^{\circ}\text{C} \pm 70^{\circ}\text{C}$
- 2. 额定值: 2.5A/5A/7A AC 125V 250V AC
- 3. 绝缘电阻:  $100\text{M}\Omega$
- 4. 耐电压: 2500V AC
- 5. 接触电阻:  $30\text{M}\Omega$
- 6. 寿命: 10000次
- 结构特性 插拔力: 13.6N~68N
- 端子强度: 60N
- 盐雾测试:  $35 \pm 2^{\circ}\text{C}$  24/h
- 耐环境性能 耐寒性能  $-20 \pm 2^{\circ}\text{C}$  96/h
- 耐热性能  $100 \pm 2^{\circ}\text{C}$  96/h
- 耐湿性能  $40 \pm 2^{\circ}\text{C}$  相对湿度90~95% 96/h




東莞市高迪電子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5  $\pm 0.2$   
Above 5 ~ 15  $\pm 0.3$   
Above 15 ~ 30  $\pm 0.4$   
Above 30 ~ 50  $\pm 0.5$   
Angle  $\pm 0.3^{\circ}$

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE
Ming Ming Zou	10/31/13
CHECKED BY:	DATE
Ning Ning Su	10/31/13
APPROVED BY:	DATE
Jia Xiang	10/31/13

MAT'L	TITLE	SWITCH
FINISH	MODLE	AC POWER SOCKET
SCALE	DWG NO.	GD-DB-8-16F
SHEET NO.	PART NO.	
1 of 1		

SIZE  
A4  
VER  
R

ITEM NO.	DESCRIPTION	DRAWN	DATE