

### SPECIFICATION

#### A: MATERIAL:

1. HOUSING & COVER: PC(BLACK), UL 94V-0
2. HANDLE: PC(RED), UL 94V-0
3. DOOR: IRON ALLOY, NICKEL PLATED
4. TERMINAL: COPPER ALLOY, TIN PLATED
5. SPRING: IRON ALLOY, NATURE

#### B: CHARACTERISTICS:

1. RATING: 10A 250V~ TUV,CCC  
15A 250V~ UL
2. INSULATION RESISTANCE: 100MΩ MIN, AT 500V DC
3. ELECTRIC STRENGTH: AC 2000V FOR ONE MINUTE
4. PREVENT SHEDDING FORCE: 10KG MIN.


#### C: APPROVALS:

UL, CUL, TUV & CCC

 東莞市高迪電子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD. ANGEL'S  UNITS MM

DRAWN BY: DATE  
Ming Ming Zou 10/31/13

CHECKED BY: DATE  
Ning Ning Su 10/31/13

APPROVED BY: DATE  
Jia Xiang 10/31/13

MAT'L		TITLE	SWITCH
FINISH		MODLE	AC POWER SOCKET
SCALE	1:1	DWG NO.	GD-GD-BT-13-1AB
SHEET NO.	1 of 1	PART NO.	
			SIZE A4
			VER R

ITEM NO.	DESCRIPTION	DRAWN	DATE