

技术参数:


- 1、额定电器性能: 3~16A 125/250VAC (UL;CUL) ;
- 2、动作时间标准: 环境温度25°C电流200% (6~32A) 时3到60秒内断开
- 3、耐压: 1500VAC/0.5mA/1min无闪络、无击穿;
- 4、机械寿命: ≥10000次;



東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Ming Ming Zou
DATE: 07/10/13

CHECKED BY: Ning Ning Su
DATE: 07/10/13

APPROVED BY: Jia Xiang
DATE: 07/10/13

MAT'L		TITLE	SWITCH
FINISH		MODLE	SWITCH
SCALE	2:1	DWG NO.	GD-HW-001-16--BF
SHEET NO.	1 of 1	PART NO.	
		SIZE	A4
		VER	R1

1	更新開關位置	Jack	071013
ITEM NO.	DESCRIPTION	DRAWN	DATE