



Technical characteristics

SPECIFICATION: 15 A max. @ 125 VAC.
 10 A max. @ 250 VAC.
 MECHANICAL LIFE: 40,000 make-and-break cycles.
 CONTACT RESISTANCE: 50mΩ max. initial @2-4VDC
 100mA for both silver.
 INSULATION RESISTANCE: 1000 MΩ min.
 DIELECTRIC STRENGTH: 1500 VAC min.
 OPERATING TEMPERATURE: -30°C to +85°C.

Materials

CASE: PF (UL 94V-0)
 HOUSING: SPCC.
 ACTUATOR: Alloy, nickel plated.
 BUSHING: Alloy, nickel plated.
 CONTACT/TERMINALS: Copper alloy silver plated.
 RoHS

東莞市高迪電子有限公司
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	Large toggle switch
Ming Ming Zou	07/23/13	FINISH	MODLE	Large toggle switch
CHECKED BY:	DATE	SCALE	DWG NO.	GD-KN3-A-101-AA-M
Ning Ning Su	07/23/13	SHEET NO.	PART NO.	
APPROVED BY:	DATE			SIZE
Jia Xiang	07/23/13			A4
				VER
				R2

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE