

安装尺寸 (Mounting)



ON - OFF - ON

电路图 (Circuitry)

**Technical characteristics**

SPECIFICATION: 15 A max. @ 125 VAC.  
 10 A max. @ 250 VAC.  
 MECHANICAL LIFE: 40,000 make-and-break cycles.  
 ELECTRICAL LIFE: 10,000 make-and-break cycles.  
 CONTACT RESISTANCE: 50mΩ max. initial @2-4VDC  
 100mA for both silver.  
 INSULATION RESISTANCE: 1000 MΩ min.  
 DIELECTRIC STRENGTH: 1500 VAC min.  
 OPERATING TEMPERATURE: -30°C to +85°C.

**Materials**

CASE: PF (UL 94V-0)  
 HOUSING: SPCC, nickel plated.  
 ACTUATOR: Alloy.  
 BUSHING: Alloy.  
 CONTACT/TERMINALS: Copper alloy silver plated.  
 RoHS

注: ①~⑥ 为重点检测尺寸;  
 图纸仅供参考, 详细以实物为准。




**东莞市高迪电子有限公司**  
**DONG GUAN GAO DI ELECTRONICS CO., LTD**

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: DATE  
 Ming Ming Zou 07/23/13  
 CHECKED BY: DATE  
 Ning Ning Su 07/23/13  
 APPROVED BY: DATE  
 Jia Xiang 07/23/13

MAT'L	TITLE	Large toggle switch
FINISH	MODLE	Large toggle switch
SCALE 1:1	DWG NO.	GD-KN3-A-103-L3P-RS
SHEET NO. 1 of 1	PART NO.	

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE	A4
VER	R2