



注 圖紙僅供參考，詳細以實物為準。

标注 A - G 为重点检测尺寸

手柄位置及导通端子示意图

Model NO.	POS. 1	POS. 2	POS. 3
103	ON	OFF	ON
SCHEMATIC		OPEN	

Technical characteristics

SPECIFICATION: 3 A max. @ 125 VAC.
 1.5 A max. @ 250 VAC.
MECHANICAL LIFE: 40,000 make-and-break cycles.
CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC
 100mA for both silver.
INSULATION RESISTANCE: 1000 MΩ min.
DIELECTRIC STRENGTH: 1000 VAC min.
OPERATING TEMPERATURE: -25°C to +85°C.

Materials

CASE: PPA (UL 94V-0)
CAP: PA66
HOUSING: Stainless Steel.
ACTUATOR: Alloy, nickel plated.
BUSHING: Alloy, nickel plated.
CONTACT/TERMINALS: Copper alloy silver plated.
RoHS



東莞市高迪電子有限公司
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	Medium sized switch
Ming Ming Zou	07/23/13			
CHECKED BY:	DATE	FINISH	MODLE	Medium sized switch
Ning Ning Su	07/23/13			
APPROVED BY:	DATE	SCALE	DWG NO.	GD-MR-0-103-A09-0001-RS
Jia Xiang	07/23/13	1:1	PART NO.	
SHEET NO.	1 of 1			SIZE A4
				VER R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012