

M12*0.75

手柄位置及导通端子示意图

	POS. 1	POS. 2	POS. 3
Model NO.			
123	(ON)	OFF	(ON)
SCHEMATIC		OPEN	

Technical characteristics

SPECIFICATION: 5 A max. @ 125 VAC.
2 A max. @ 250 VAC.

MECHANICAL LIFE: 40,000 make-and-break cycles.

ELECTRICAL LIFE: 10,000 make-and-break cycles.

CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC
100mA for both silver.

INSULATION RESISTANCE: 1000 MΩ min.

DIELECTRIC STRENGTH: 1500 VAC min.

OPERATING TEMPERATURE: -25°C to +85°C.

Materials

CASE: PPA (UL 94V-0)

HOUSING: Stainless Steel.

ACTUATOR: Alloy, chrome plated.

BUSHING: Alloy, nickel plated.

CONTACT/TERMINALS: Copper alloy silver plated.

RoHS




东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Ming Ming Zou
DATE: 07/23/13

CHECKED BY: Ning Ning Su
DATE: 07/23/13

APPROVED BY: Jia Xiang
DATE: 07/23/13

MAT'L

FINISH

SCALE

SHEET NO.

1:1

1 of 1

TITLE Medium sized switch

MODLE Medium sized switch

DWG NO. GD-MT-0-102-D001-D000-LF

PART NO.

SIZE A4
VER R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012