

手柄位置及导通端子示意图

Model NO.	POS. 1	POS. 2	POS. 3
234	ON	ON	ON
SCHEMATIC			

### Technical characteristics

SPECIFICATION: 5 A max. @ 125 VAC.

2 A max. @ 250 VAC.

MECHANICAL LIFE: 40,000 make-and-break cycles.

CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC  
100mA for both silver.

INSULATION RESISTANCE: 1000 MΩ min.

DIELECTRIC STRENGTH: 1500 VAC min.

OPERATING TEMPERATURE: -30°C to +85°C.

### Materials

CASE: PPA (UL 94V-0)

HOUSING: Stainless Steel.

ACTUATOR: Alloy, chrome plated.

BUSHING: Alloy, nickel plated.

CONTACT/TERMINALS: Copper alloy silver plated.

RoHS




东莞市高迪电子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Ming Ming Zou  
DATE: 07/23/13  
CHECKED BY: Ning Ning Su  
DATE: 07/23/13  
APPROVED BY: Jia Xiang  
DATE: 07/23/13

MAT'L	TITLE	Medium sized switch
FINISH	MODLE	Medium sized switch
SCALE: 1:1	DWG NO.	GD-MT-0-102-D002-D000-LF
SHEET NO. 1 of 1	PART NO.	

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012

SIZE A4  
VER R2