



手柄位置及导通端子示意图

	POS. 1	POS. 2	POS. 3
Model NO.			
234	ON	ON	ON
SCHEMATIC			

**Technical characteristics**

SPECIFICATION: 5 A max. @ 125 VAC.  
 2 A max. @ 250 VAC.  
 MECHANICAL LIFE: 40,000 make-and-break cycles.  
 CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC  
 100mA for both silver.  
 INSULATION RESISTANCE: 1000 MΩ min.  
 DIELECTRIC STRENGTH: 1500 VAC min.  
 OPERATING TEMPERATURE: -30°C to +85°C.

**Materials**

CASE: PPA (UL 94V-0)  
 HOUSING: Stainless Steel.  
 ACTUATOR: Alloy, chrome plated.  
 BUSHING: Alloy, nickel plated.  
 CONTACT/TERMINALS: Copper alloy silver plated.  
 RoHS



ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012

TOLERANCE UNLESS OTHERWISE STATED:	Up to 5 ±0.2	Above 5 ~ 15 ±0.3	Above 15 ~ 30 ±0.4	Above 30 ~ 50 ±0.5	Angle ±0.3°
	3RD. ANGEL'S	UNITS	MM		

DRAWN BY:	DATE	MAT'L	TITLE	Medium sized switch
Ming Ming Zou	07/23/13		MODLE	Medium sized switch
CHECKED BY:	DATE	FINISH	DWG NO.	GD-MT-0-102-D004-D000-LF
Ning Ning Su	07/23/13		SHEET NO.	1 of 1
APPROVED BY:	DATE	SCALE	PART NO.	
Jia Xiang	07/23/13	1:1		

SIZE A4  
VER R2