



手柄位置及导通端子示意图

**Technical characteristics**

**SPECIFICATION:** 3 A max. @ 125 VAC.  
 1.5 A max. @ 250 VAC.  
**MECHANICAL LIFE:** 40,000 make-and-break cycles.  
**CONTACT RESISTANCE:** 20mΩ max. initial @2-4VDC  
 100mA for both silver.  
**INSULATION RESISTANCE:** 1000 MΩ min.  
**DIELECTRIC STRENGTH:** 1000 VAC min.  
**OPERATING TEMPERATURE:** -25°C to +85°C.

**Materials**

**CASE:** PPA (UL 94V-0)  
**CAP:** PA66  
**HOUSING:** Stainless Steel.  
**ACTUATOR:** Alloy, nickel plated.  
**BUSHING:** Alloy, nickel plated.  
**CONTACT/TERMINALS:** Copper alloy silver plated.  
 RoHS

	POS. 1	POS. 2	POS. 3
Model NO.			
103	ON	OFF	ON
SCHEMATIC		OPEN	

东莞市高迪电子有限公司  
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	Medium sized switch
Ming Ming Zou	07/23/13			
CHECKED BY:	DATE	FINISH	MODLE	Medium sized switch
Ning Ning Su	07/23/13			
APPROVED BY:	DATE	SCALE	DWG NO.	GD-MT-0-103-A101-M200-RS
Jia Xiang	07/23/13	1:1	PART NO.	
SHEET NO.	1 of 1			SIZE A4
				VER R2

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE