



手柄位置及导通端子示意图

Technical characteristics

SPECIFICATION: 5 A max. @ 125 VAC.
 2 A max. @ 250 VAC.
 MECHANICAL LIFE: 40,000 make-and-break cycles.
 CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC
 100mA for both silver.
 INSULATION RESISTANCE: 1000 MΩ min.
 DIELECTRIC STRENGTH: 1500 VAC min.
 OPERATING TEMPERATURE: -30°C to +85°C.

Materials

CASE: PPA (UL 94V-0)
 HOUSING: Stainless Steel.
 ACTUATOR: Alloy, chrome plated.
 BUSHING: Alloy, nickel plated.
 CONTACT/TERMINALS: Copper alloy silver plated.
 RoHS

| Model NO. | POS. 1 | POS. 2 | POS. 3 |
|-----------|--------|--------|--------|
| 234 | ON | ON | ON |
| SCHEMATIC | | | |

东莞市高迪电子有限公司
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

| | | | | |
|---------------|----------|----------|---------|---------------------|
| DRAWN BY: | DATE | MAT'L | TITLE | Medium sized switch |
| Ming Ming Zou | 07/23/13 | | | |
| CHECKED BY: | DATE | FINISH | MODLE | Medium sized switch |
| Ning Ning Su | 07/23/13 | | | |
| APPROVED BY: | DATE | SCALE | DWG NO. | GD-MT-0-103-L001 |
| Jia Xiang | 07/23/13 | 1:1 | | |
| SHEET NO. | 1 of 1 | PART NO. | | |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|----------|-------------|----------|--------|
| 2 | 公差及料號更新 | Jack | 072313 |
| 1 | 圖面更新 | Frank Wu | 021012 |