

SCHMATIC



SPECIFICATION

1. Rating : DC 30V 0.5A ;
2. Contact resistance :  $\leq 30m\Omega$  ;
3. Insulation resistance :  $\geq 100M\Omega$  ;
4. Withstand voltage : 500VAC ;
5. Insertion and extraction force : 3-20N
6. life test : 5,000 cycles °

4	CONTACT FOOT	1	Phosphor Bronze	Ag-Plated
3	CONTACT FOOT	1	Phosphor Bronze	Ag-Plated
2	CONTACT FOOT	1	Phosphor Bronze	Ag-Plated
1	HOUSING	1	PBT	
NO.	DESCRIPTION	QTY	MATERIAL	REMARK




东莞市高迪电子有限公司  
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	06/19/17		MODLE	PHONE JACK
CHECKED BY:	DATE	FINISH	DWG NO.	GD-PJS-3501Y
Jacky Chen	06/19/17		PART NO.	
APPROVED BY:	DATE	SCALE	1 : 1	
Tony Kao	06/19/17	SHEET NO.	1 of 1	

ITEM NO.	DESCRIPTION	DRAWN	DATE