

SPECIFICATION

- 1. Rating : DC 30V, 0.5A ;
- 2. Contact resistance : $\leq 30m\Omega$;
- 3. Insulation resistance : $\geq 100M\Omega$;
- 4. Withstand voltage : 500VAC ;
- 5. Insertion and extraction force : 3-20N;
- 6. life test : 5,000 cycles °

Technology Request:

- 1. Outlook: No burr, no hurt.
- 2. Electronic performance:
 - a: Insulation resistance: Above DC500V/100M Ω ;
 - b: Endure voltage: AC500V at 1 minute;
 - c: Contact resistance: Under 30m Ω ;
- 3. Insertion force & withdrawal force: 0.3-3kgf.
- 4. Salt spray test: 24H.
- 5. Meet RoHS.
- 6. Remark * is important specification.




东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ± 0.2
 Above 5 ~ 15 ± 0.3
 Above 15 ~ 30 ± 0.4
 Above 30 ~ 50 ± 0.5
 Angle $\pm 0.3^\circ$

3RD. ANGEL'S



UNITS

MM

DRAWN BY: DATE

Jack Lu 06/19/17

CHECKED BY: DATE

Jacky Chen 06/19/17

APPROVED BY: DATE

Tony Kao 06/19/17

MAT'L

FINISH

SCALE

SHEET NO.

TITLE

MODLE

DWG NO.

PART NO.

Plug

Audio Plug

GD-PJT-3503L38

SIZE
A4
VER
R

ITEM NO.	DESCRIPTION	DRAWN	DATE

7

7