

标注: ①-⑧尺寸的重点检验尺寸

Technical characteristics

SPECIFICATION: 3 A max. @ 125 VAC.

1.5 A max. @ 250 VAC.

MECHANICAL LIFE: 40,000 make-and-break cycles.

CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC

100mA for both silver.

INSULATION RESISTANCE: 1000 MΩ min.

DIELECTRIC STRENGTH: 1000 VAC min.

OPERATING TEMPERATURE: -25°C to +85°C.

Materials

CASE: PPA (UL 94V-0)

CAP: PA66

HOUSING: Stainless Steel.

ACTUATOR: Alloy, nickel plated.

BUSHING: Alloy, nickel plated.

CONTACT/TERMINALS: Copper alloy silver plated.

RoHS

SWITCH FUNCTION

Model NO.	POS.1	POS.2	POS.3
103	ON	OFF	ON
SCHEMATIC		OPEN	




东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: DATE
Ming Ming Zou 07/23/13

CHECKED BY: DATE
Ning Ning Su 07/23/13

APPROVED BY: DATE
Jia Xiang 07/23/13

MAT'L

FINISH

SCALE

SHEET NO.

TITLE

MODLE

DWG NO.

PART NO.

Medium sized switch

Medium sized switch

GD-SA-0-103-D04-0004-RS

SIZE
A4
VER
R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012