

安装孔尺寸

手柄位置及导通端子示意图

	POS.1	POS.2	POS.3
Model NO.			
102	ON	NONE	ON
SCHEMATIC		NONE	

**Technical characteristics**

SPECIFICATION: 3 A max. @ 125 VAC.  
 1.5 A max. @ 250 VAC.  
 MECHANICAL LIFE: 40,000 make-and-break cycles.  
 CONTACT RESISTANCE: 20mΩ max. initial @2-4VDC  
 100mA for both silver.  
 INSULATION RESISTANCE: 1000 MΩ min.  
 DIELECTRIC STRENGTH: 1000 VAC min.  
 OPERATING TEMPERATURE: -25°C to +85°C.

**Materials**


CASE: PPA (UL 94V-0)  
 CAP: PA66  
 HOUSING: Stainless Steel.  
 ACTUATOR: Alloy, nickel plated.  
 BUSHING: Alloy, nickel plated.  
 CONTACT/TERMINALS: Copper alloy silver plated.  
 RoHS



东莞市高迪电子有限公司  
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: DATE  
 Ming Ming Zou 07/23/13  
 CHECKED BY: DATE  
 Ning Ning Su 07/23/13  
 APPROVED BY: DATE  
 Jia Xiang 07/23/13

MAT'L  
 FINISH  
 SCALE 1:1  
 SHEET NO. 1 of 1

TITLE miniature switch  
 MODLE miniature switch  
 DWG NO. GD-SA1-0-102-C02-0000-RS  
 PART NO.

SIZE A4  
 VER R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012