



三档滑动开关

1. 滑动开关型号 SLIDE SWITCH MODEL: SFD-1-23
2. PCB端子 PCB MOUNT TERMINAL;
双刀三掷 DOUBLE POLE THREE THROW
3. 额定值 RATING: ▲ 16(4)A 125/250VAC μ T105
10(2)A 125/250VAC μ T85
4. 接触电阻 CONTACT RESISTANCE: <50m Ω (INITIAL)
5. 绝缘电阻 INSULATION RESISTANCE: \geq 100M Ω (DC500V/1MIN)
6. 介电强度 DIELECTRIC STRENGTH: 1500V /5mA /1MIN
7. 机械寿命 MECHANICAL LIFE: >50000 CYCLES
8. 电气寿命 ELECTRICAL LIFE: >10000 CYCLES
9. 端子手工焊接条件 SOLDER ABILITY OF TERMINAL: MAX260°C. 3S
10. 操作力 OPERATION FORCE: 550 \pm 150gf
11. 所有部件均使用环保材料 ALL MATERIALS ARE RoHS COMPLIANT

NO.	PARTS	MATERIALS	QTY	FINISH
5	CONTACT CLIP	PBS STRIP	1	Ag PLATED
4	TERMINAL	BRASS	3	Ag PLATED
3	BASE	PHENOLIC RESIN	1	NATURAL
2	FRAME	STEEL STRIP	1	Ni PLATED
1	KNOB	POM	1	BLACK

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增SPEC	Jack	111914
1	新增尺寸	Jack	061614


东莞市高迪电子有限公司
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	\pm 0.2
Above 5 ~ 15	\pm 0.3
Above 15 ~ 30	\pm 0.4
Above 30 ~ 50	\pm 0.5
Angle	\pm 0.3°

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Ming Ming Zou	11/19/14			
CHECKED BY:	DATE	FINISH	MODLE	SLIDE SWITCH
Ning Ning Su	11/19/14			
APPROVED BY:	DATE	SCALE	DWG NO.	GD-SFD-1-23CAB
Jia Xiang	11/19/14	1:1		
SHEET NO.	1 of 1	PART NO.		

SIZE
A4
VER
R2