

四档滑动开关

1. 滑动开关型号 SLIDE SWITCH MODEL: SFD-1-24DAS
2. 焊线端子 SOLDER CONNECTOR TYPE;
双刀四掷 DOUBLE POLE FOUR THROW
3. 额定值 RATING: ▲ 16(4)A 125/250VAC μ T105
10(2)A 125/250VAC μ T105

▲ 16A 125/250VAC μ T105
10(2)A 125/250VAC μ T85

4. 接触电阻 CONTACT RESISTANCE: <50m Ω (INITIAL)
5. 绝缘电阻 INSULATION RESISTANCE: \geq 100M Ω (DC500V/1MIN)
6. 介电强度 DIELECTRIC STRENGTH: 1500V /5mA /1MIN
7. 机械寿命 MECHANICAL LIFE: >50000 CYCLES
8. 电气寿命 ELECTRICAL LIFE: >10000 CYCLES
9. 端子手工焊接条件 SOLDER ABILITY OF TERMINAL: MAX260°C. 3S
10. 操作力 OPERATION FORCE: 550 \pm 150gf
11. 所有部件均使用环保材料 ALL MATERIALS ARE RoHS COMPLIANT

NO.	PARTS	MATERIALS	QTY	FINISH
5	CONTACT CLIP	PBS STRIP	1	Ag PLATED
4	TERMINAL	BRASS	3	Ag PLATED
3	BASE	PHENOLIC RESIN	1	NATURAL
2	FRAME	STEEL STRIP	1	Ni PLATED
1	KNOB	POM	1	BLACK




东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	\pm 0.2
Above 5 ~ 15	\pm 0.3
Above 15 ~ 30	\pm 0.4
Above 30 ~ 50	\pm 0.5
Angle	\pm 0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: DATE
Ming Ming Zou 11/19/14

CHECKED BY: DATE
Ning Ning Su 11/19/14

APPROVED BY: DATE
Jia Xiang 11/19/14

MAT'L	TITLE	MODLE	DWG NO.	PART NO.	SIZE
	SWITCH	SLIDE SWITCH	GD-SFD-1-24DAS		A4
SCALE 1:1					VER R2
SHEET NO. 1 of 1					

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增SPEC	Jack	111914
1	新增尺寸	Jack	061614