



产品参数		
耐电压	DC 500V	
额定电流	20A/16#	20A
瞬时电流	40A/16#	40A
接触电阻	0.60mΩ	0.80mΩ
插拔寿命	100times	
防打火	否	
带卡扣	否	
接线推荐		
AWG	温升60°C	温升80°C
12#	40A	45A
14#	30A	30A
16#	25A	30A
18#	20A	25A


**東莞市高迪電子有限公司**  
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 - 15 ±0.3, Above 15 - 30 ±0.4, Above 30 - 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Ming Ming Zou 07/23/13  
 CHECKED BY: Ning Ning Su 07/23/13  
 APPROVED BY: Jia Xiang 07/23/13

MAT'L		TITLE	connector
FINISH		MODLE	connector
SCALE	1:1	DWG NO.	GD-TX-15018E-M
SHEET NO.	1 of 1	PART NO.	
		SIZE	A4
		VER	R2

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE