



产品参数		
耐电压	DC 500V	
额定电流	20A/16#	20A
瞬时电流	40A/16#	40A
接触电阻	0.60mΩ	0.80mΩ
插拔寿命	100times	
防打火	否	
带卡扣	否	
接线推荐		
AWG	温升60°C	温升80°C
12#	40A	45A
14#	30A	30A
16#	25A	30A
18#	20A	25A

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012



東莞市高迪電子有限公司  
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:  
Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: Ming Ming Zou 07/23/13  
CHECKED BY: Ning Ning Su 07/23/13  
APPROVED BY: Jia Xiang 07/23/13

MAT'L  
FINISH  
SCALE 1 : 1  
SHEET NO. 1 of 1  
TITLE connector  
MODLE connector  
DWG NO. GD-TX-15018L-G  
PART NO.

SIZE A4  
VER R2