


产品型号: 推荐应用: 锂电池/控制器
 产品颜色: 金属材质: 镀金
 瞬时电流: 40A/16# 推荐线规: 12#/14#/16#
 额定电流: 20A/16# 绝缘材质: PA66
 接触电阻: 0.60mΩ 工作温度: -20°C to 120°C
 耐电压: DC 500V 推荐使用次数: 100times
 阻燃等级: UL94-V0



东莞市高迪电子有限公司
 DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: DATE
 Ming Ming Zou 07/23/13
 CHECKED BY: DATE
 Ning Ning Su 07/23/13
 APPROVED BY: DATE
 Jia Xiang 07/23/13

MAT'L		TITLE	connector
FINISH		MODLE	connector
SCALE	1:1	DWG NO.	GD-TX-60E-F-M
SHEET NO.	1 of 1	PART NO.	

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE A4
 VER R2