


耐电压	DC 500V	金属件	H59-1
额定电流	20A	镀厚金	0.03μm
接触电阻	0.60mΩ	外壳	PA66阻燃材质
绝缘电阻	2000MΩ	插入力	1.8kg-4.5kg
瞬时电流	40A	拔出力	1.8kg-4.5kg
温升	20A 4h <60°C	阻燃等级	UL94-V0
爬电距离	2.9mm	防护等级	IP40
使用温度	-20°C~120°C	盐雾	48h


东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: DATE
 Ming Ming Zou 07/23/13
 CHECKED BY: DATE
 Ning Ning Su 07/23/13
 APPROVED BY: DATE
 Jia Xiang 07/23/13

MAT'L		TITLE	connector
FINISH		MODLE	connector
SCALE	1:1	DWG NO.	GD-TX-60E-M
SHEET NO.	1 of 1	PART NO.	

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE
 A4
 VER
 R2