



产品型号: 推荐应用: 锂电池/控制器
 产品颜色: 金属材质: 镀金
 瞬时电流: 60A/12# 推荐线规: 8#/10#/12#
 额定电流: 30A/12# 绝缘材质: PA6
 接触电阻: 0.40mΩ 工作温度: -20°C to 120°C
 耐电压: DC 500V 推荐使用次数: 100times
 阻燃等级: UL94-V0

東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5, Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	ENCODER
Ming Ming Zou	07/23/13			
CHECKED BY:	DATE	FINISH	MODLE	ENCODER
Ning Ning Su	07/23/13			
APPROVED BY:	DATE	SCALE	DWG NO.	GD-TX-90E-G
Jia Xiang	07/23/13	1:1	PART NO.	
SHEET NO.	1 of 1			SIZE A4
				VER R2

2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012
ITEM NO.	DESCRIPTION	DRAWN	DATE