

ZS-QS10-S防打火插壳 无人机/锂电动力连接器供电插头


产品型号 : ZS-QS10-S	产品颜色 : 黑色
Product model: QS10-S	Color: Black
瞬间电流 : 240A	额定电流 : 180A
Instantaneous current: 240A	Current rating: 180A
接触电阻 : 0.51mΩ	额定电压 : DC 500V
Contact Resistance: 0.51mΩ	Voltage rating: DC 500V
阻燃等级 : UL94 V0	推荐应用 : 电池/控制器
Flammability: UL94 V0	Recommended application: battery/controller
金属材质 : 铜 镀金	推荐线规格 : 4AWG-10AWG
Contact material: Copper Plate	Poles: 4AWG-10AWG
绝缘材质 : PA	工作温度 : -20°C to 120°C
Material: PA	Working Temperature: -20°C to 120°C
推荐使用次数 : 1000 TIMES	
Recommended TIMES: 1000 TIMES	



东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Ming Ming Zou	07/23/13
CHECKED BY:	DATE
Ning Ning Su	07/23/13
APPROVED BY:	DATE
Jia Xiang	07/23/13

MAT'L	FINISH	SCALE	SHEET NO.
		1:1	1 of 1

TITLE	MODLE	DWG NO.	PART NO.
connector	connector	GD-qs10-Model_1	

SIZE	VER
A4	R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	公差及料號更新	Jack	072313
1	圖面更新	Frank Wu	021012