


- 1、FUNCTION: OFF-ON
- 2、RATING: UL: TV-5  
ENEC VDE/CQC: 8A/128A μ 250V~T85
- 3、OPERATION FORCE: 700±300g.f
- 4、CONTACT RESISTANCE: ≤ 50 mΩ
- 5、INSULATION RESISTANCE: ≥ 100 MΩ
- 6、DIELECTRIC WITHSTAND: TERMINAL TO BUTTON 3000VAC/5mA/1MINTUE  
TERMINAL TO TERMINAL 1500VAC/5mA/1MINTUE

7、TRAVEL:

FULL TRAVEL	4.0±0.5mm
LOCK TRAVEL	2.5±0.5mm



注: "\*"□表示关键尺寸(3个).

NO.	PARTS	MATERIALS	Q'TY	TOLERANCE UNLESS SPECIFIED			
8							
7							
6				WITHIN 1.5mm : ±0.1mm	A	2012-8-13	初版
5	SPRING	SUS	1	NATURAL	ISSUE	DATE	DESCRIPTIONS OF REVISION
4	CAM STICK	SUS	1	NATURAL	TITLE : PUSH SWITCH		
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	UNIT : mm		DRWG NO.:
2	COVER	PA66	1	BLACK	MODEL:		SCALE: 5:1
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD	DWN.		2012-8-13
					CHK'D		
					APPD.		2012-8-13

东莞市高迪电子有限公司