



MARK

SPEC:

A. Material:

- 1.Housing: PA66
- 2.Terminal: COPPER ALLOY, TIN PLATED

B.Electrical Characteristics:

- 1.Rating: 2.5A 250V~
(JL,CUL,CCC,VDE,SEMKO,NEMKO,FIMKO,DEMKO,KC)
- 2.Electric Strength: AC 2,000 V FOR ONE MINUTE
- 3.Insulation Resistance: 100MΩ MIN, AT 500V DC

C.Approvals:

UL, CUL, CCC, VDE, SEMKO, NEMKO, FIMKO, DEMKO, KC

普通公差

COMMON TOLERANCE :

| | |
|---------------|-------|
| UP TO 5 | ±0.20 |
| ABOVE 5 TO 30 | ±0.30 |
| ABOVE 30 | ±0.50 |
| ANGULAR | ±5° |



东莞市高迪电子有限公司

| | | | | | | | | |
|------|------|----------------------|-------|----------------|------------|-------------------|--------------------|---------------|
| REV. | DATE | REVISION DESCRIPTION | ISSUE | 单位 UNIT | mm | 投影 PROJECTED | 品名 PRODUCT NAME | AC POWER JACK |
| | | | | 绘图 DRAWN BY | 林晓良 | 核对 CHECKED BY | 型号 MODEL NO. | |
| | | | | 日期 DATE | 19. 08. 12 | 核准 APPROVAL BY | 料号 PART NO. | KD-AC电源插座 |