



SPECIFICATIONS

1. Rating : DC 10V , 1 mA Max ;
2. Circuit : 1C - 1P ;
3. Operating force : 25 ±10 gf ;
4. Contact resistance : 100 mΩ Max ;
5. Travel : 0.25 ± 0.1 mm ;
6. Life : 150,000 Cycles Min °
(each upright and opposite roate)



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 - 15 ±0.3
Above 15 - 30 ±0.4
Above 30 - 50 ±0.5
Angle ±0.3

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:

DATE

Frank Wu

10/17/11

MAT'L

TITLE

ENCODER

CHECKED BY:

DATE

Jacky Chen

10/17/11

FINISH

MODLE

ENCODER

APPROVED BY:

DATE

Tony Kao

10/17/11

SCALE

1 : 1

DWG NO.

K50-A

SIZE

A4

SHEET NO.

1 of 1

PART NO.

K50-A

VER

A

ITEM NO	DESCRIPTION	DRAWN	DATE

A B C D E F G H I J