


- SPECIFICATIONS**
1. Rating : DC 10V , 1 mA Max ;
  2. Circuit : 1C - 1P ;
  3. Operating force : 25 ±10 gf ;
  4. Contact resistance : 100 mΩ Max ;
  5. Travel : 0.25 ± 0.1 mm ;
  6. Life : 150,000 Cycles Min °  
(each upright and opposite roate)

 **东莞市高迪电子有限公司**  
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 - 15 ±0.3  
 Above 15 - 30 ±0.4  
 Above 30 - 50 ±0.5  
 Angle ±0.3

3RD. ANGEL'S  UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	ENCODER
Frank Wu	10/17/11		MODLE	ENCODER
CHECKED BY:	DATE	SCALE	DWG NO.	K50-A
Jacky Chen	10/17/11	1 : 1	PART NO.	K50-A
APPROVED BY:	DATE	SHEET NO.	1 of 1	SIZE A4
Tony Kao	10/17/11			VER A

ITEM NO.	DESCRIPTION	DRAWN	DATE