



A: Output signal A
B: Output signal B

SPECIFICATIONS

1. Rating : DC 10V , 1 mA Max ;
2. Circuit : 1C - 1P ;
3. Operating force : 25 ±10 gf ;
4. Contact resistance : 100 mΩ Max ;
5. Travel : 0.25 ± 0.1 mm ;
6. Life : 150,000 Cycles Min °
 (each upright and opposite roate)



东莞市高迪电子有限公司
 Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
 OTHERWISE STATED :

Up to 5 ±0.2
 Above 5 - 15 ±0.3
 Above 15 - 30 ±0.4
 Above 30 - 50 ±0.5
 Angle ±0.3

3RD.
 ANGEL'S



UNITS

MM

DRAWN BY: Frank Wu
 CHECKED BY: Jacky Chen
 APPROVED BY: Tony Kao

DATE: 10/17/11
 DATE: 10/17/11
 DATE: 10/17/11

MAT'L
 FINISH
 SCALE

1 : 1

SHEET NO. 1 of 1

TITLE MODLE
 DWG NO. K50-A
 PART NO. K50-A

ENCODER
 ENCODER

SIZE A4
 VER A

ITEM NO.	DESCRIPTION	DRAWN	DATE