



### SPECIFICATIONS

1. Rating : DC 10V , 1 mA Max ;
2. Circuit : 1C - 1P ;
3. Operating force : 25  $\pm 10$  gf ;
4. Contact resistance : 100 m $\Omega$  Max ;
5. Travel : 0.25  $\pm 0.1$  mm ;
6. Life : 150,000 Cycles Min .  
(each upright and opposite roate)



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	$\pm 0.2$
Above 5 - 15	$\pm 0.3$
Above 15 - 30	$\pm 0.4$
Above 30 - 50	$\pm 0.5$
Angle	$\pm 0.3$

3RD. ANGEL'S

UNITS: MM

DRAWN BY:	DATE	MAT'L	TITLE	ENCODER
Frank Wu	10/17/11		MODLE	ENCODER
CHECKED BY:	DATE	SCALE	DWG NO.	K50-A
Jacky Chen	10/17/11	1 : 1	PART NO.	K50-A
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	10/17/11			
				SIZE
				A4
				VER
				A