



SPECIFICATIONS

- 1. Rating : DC 10V , 1 mA Max ;
- 2. Circuit : 1C - 1P ;
- 3. Operating force : 25 ±10 gf ;
- 4. Contact resistance : 100 mΩ Max ;
- 5. Travel : 0.25 ± 0.1 mm ;
- 6. Life : 150,000 Cycles Min °
(each upright and opposite roate)



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch JacK Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 - 15 ±0.3
 Above 15 - 30 ±0.4
 Above 30 - 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	ENCODER
Frank Wu	10/17/11			
CHECKED BY:	DATE	FINISH	MODLE	ENCODER
Jacky Chen	10/17/11			
APPROVED BY:	DATE	SCALE	DWG NO.	K50-A
Tony Kao	10/17/11	1 : 1	PART NO.	K50-A
SHEET NO.	1 of 1			SIZE A4
				VER A

ITEM NO.	DESCRIPTION	DRAWN	DATE