



SPECIFICATIONS

1. Rating : DC 10V , 1 mA Max ;
2. Circuit : 1C - 1P ;
3. Operating force : 25 ±10 gf ;
4. Contact resistance : 100 mΩ Max ;
5. Travel : 0.25 ± 0.1 mm ;
6. Life : 150,000 Cycles Min °
(each upright and opposite roate)



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 - 15 ±0.3
Above 15 - 30 ±0.4
Above 30 - 50 ±0.5
Angle ±0.3

3RD.
ANGEL'S



UNITS

MM

| | |
|--------------|----------|
| DRAWN BY: | DATE |
| Frank Wu | 10/17/11 |
| CHECKED BY: | DATE |
| Jacky Chen | 10/17/11 |
| APPROVED BY: | DATE |
| Tony Kao | 10/17/11 |

| | | |
|-----------|--------|----------------|
| MAT'L | TITLE | ENCODER |
| FINISH | MODLE | ENCODER |
| SCALE | 1 : 1 | DWG NO. K50-A |
| SHEET NO. | 1 of 1 | PART NO. K50-A |
| | | SIZE A4 |
| | | VER A |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|----------|-------------|-------|------|
| | | | |