



MODEL NO.	DC-D0239CH-x
SCHEMATIC	
CENTER PIN(X)	Ø1.30 mm
	Ø2.00 mm
	Ø2.50mm

#### SPECIFICATION

1. Rating : DC 18V, 4.0A ;
2. Contact resistance :  $\leq 50m\Omega$  ;
3. Insulation resistance :  $\geq 100M\Omega$  ;
4. Withstand voltage : 500VAC ;
5. Insertion and extraction force : 3-30N;
6. life test : 5,000 cycles °

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
7	MYLAR	1		
6	PIN TERMINAL	1	BRASS	Ti Plated over Ni
5	SHUNT TERMINAL	1	BRASS	Ti Plated over Ni
4	SPRING TERMINAL	1	BRASS	Ti Plated over Ni
3	CENTER PIN	1	COPPER	Ni-Plating
2	BOTTOM COVER	1	PA9T(Black)	
1	HOUSING	1	LCP(Black)	



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	05/13/19			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK 高温料 贴MYLAR
Jacky Chen	05/13/19			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-D0239CH-x-S214
Tony Kao	05/13/19	1 : 1	PART NO.	DC-D0239CH-x-S214
		SHEET NO.	1 of 1	SIZE A4
				VER R

ITEM NO.	DESCRIPTION	DRAWN	DATE