



配线图



电源参数: 12 (10)A 250V AC; 7 (7)A 250V AC; 8A 250V AC;  
 16A 125V AC; 18A 125V AC  
 接触电阻:  $\leq 50 \text{ m}\Omega$   
 绝缘电阻:  $\geq 100 \text{ M}\Omega$   
 介电强度: 极与极1500VAC, 极与壳3000VAC  
 环境温度: T105  
 电气寿命: 1E4

NO.	PARTS	MATERIALS	Q'TY		TOLERANCE UNLESS SPECIFIED				
8									
7									
6					WITHIN 1.5mm : $\pm 0.1 \text{ mm}$	A	2012-8-13	初版	
5	SPRING	SUS	1	NATURAL	OVER 1.5mm : $\pm 0.2 \text{ mm}$	ISSUE	DATE	DESCRIPTIONS OF REVISION	
4	CAM STICK	SUS	1	NATURAL	TITLE : VERTICAL PUSH SWITCH			UNIT : mm	DRWG NO.:
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	MODEL:			SCALE: 5:1	DWN.
2	COVER	PA66	1	BLACK	东莞市高迪电子有限公司				2012-8-13
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD				CHK'D	
								APPD.	