


配线图



电源参数: 12 (10) A 250V AC; 7 (7) A 250V AC; 8A 250V AC;
 16A 125V AC; 18A 125V AC
 接触电阻: $\leq 50\text{m}\Omega$
 绝缘电阻: $\geq 100\text{M}\Omega$
 介电强度: 极与极1500VAC, 极与壳3000VAC
 环境温度: T105
 电气寿命: 1E4

NO.	PARTS	MATERIALS	Q'TY	TOLERANCE UNLESS SPECIFIED	DATE	DESCRIPTIONS OF REVISION	APPD.
8							
7							
6				WITHIN 1.5mm : $\pm 0.1\text{mm}$ OVER 1.5mm : $\pm 0.2\text{mm}$	A	2012-8-13	初版
5	SPRING	SUS	1	NATURAL	ISSUE	DATE	APPD.
4	CAM STICK	SUS	1	NATURAL	TITLE : VERTICAL PUSH SWITCH		
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	UNIT : mm	DRWG NO.:	
2	COVER	PA66	1	BLACK	SCALE: 5:1	DWN.	2012-8-13
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD	东莞市高迪电子有限公司		
						CHK'D	2012-8-13
						APPD.	