


配线图



电源参数: 12 (10)A 250V AC; 7 (7)A 250V AC; 8A 250V AC;
 16A 125VAC; 18A 125VAC
 接触电阻: $\leq 50\text{m}\Omega$
 绝缘电阻: $\geq 100\text{M}\Omega$
 介电强度: 极与极1500VAC, 极与壳3000VAC
 环境温度: T105
 电气寿命: 1E4

NO.	PARTS	MATERIALS	Q'TY		TOLERANCE UNLESS SPECIFIED				
8					WITHIN 1.5mm : $\pm 0.1\text{mm}$	A	2012-8-13	初版	
7					OVER 1.5mm : $\pm 0.2\text{mm}$	ISSUE	DATE	DESCRIPTIONS OF REVISION	
6					TITLE : VERTICAL PUSH SWITCH			UNIT : mm	DRWG NO.:
5	SPRING	SUS	1	NATURAL	MODEL:			SCALE: 5:1	DWN.
4	CAM STICK	SUS	1	NATURAL	东莞市高迪电子有限公司				2012-8-13
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED				CHK'D	
2	COVER	PA66	1	BLACK				APPD.	
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD					