


配线图



电源参数: 12 (10)A 250V AC; 7 (7)A 250V AC; 8A 250V AC;
 16A 125V AC; 18A 125V AC
 接触电阻: $\leq 50 \text{ m}\Omega$
 绝缘电阻: $\geq 100 \text{ M}\Omega$
 介电强度: 极与极 1500VAC, 极与壳 3000VAC
 环境温度: T105
 电气寿命: 1E4

8					TOLERANCE					
7					UNLESS SPECIFIED					
6					WITHIN 1.5mm : $\pm 0.1 \text{ mm}$	A	2012-8-13	初版		
5	SPRING	SUS	1	NATURAL	OVER 1.5mm : $\pm 0.2 \text{ mm}$	ISSUE	DATE	DESCRIPTIONS OF REVISION		APPD.
4	CAM STICK	SUS	1	NATURAL	TITLE : VERTICAL PUSH SWITCH			UNIT : mm	DRWG NO.:	
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	MODEL:			SCALE: 5:1	DWN.	2012-8-13
2	COVER	PA66	1	BLACK	东莞市高迪电子有限公司			CHK'D		2012-8-13
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD				APPD.		
NO.	PARTS	MATERIALS	Q'TY							