


印制板开孔尺寸(±0.1mm)



配线图



电源参数: 12(10)A 250V AC; 12A 250VAC; 16A 125V AC  
 接触电阻:  $\leq 50\text{m}\Omega$   
 绝缘电阻:  $\geq 100\text{M}\Omega$   
 介电强度: 极与极1500VAC, 极与壳3000VAC  
 环境温度: T125  
 电气寿命: 2E4

NO.	PARTS	MATERIALS	Q'TY		TOLERANCE UNLESS SPECIFIED				
8					WITHIN 1.5mm : ±0.1mm	A	2012-8-13	初版	
7					OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
5	SPRING	SUS	1	NATURAL	TITLE : VERTICAL PUSH SWITCH				UNIT : mm
4	CAM STICK	SUS	1	NATURAL	MODEL:				DRWG NO.:
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED					SCALE: 5:1
2	COVER	PA66	1	BLACK					DWN.
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD					2012-8-13
					东莞市高迪电子有限公司				CHK'D
									APPD.
									2012-8-13