


配线图



电源参数: 2A 250V AC 4A 125V AC
 接触电阻: $\leq 50m\Omega$
 绝缘电阻: $\geq 100M\Omega$
 介电强度: 极与极1500VAC, 极与壳3000VAC
 环境温度: T85
 电气寿命: 1E4

| | | | | | | | | | |
|-----|-----------|--------------------|------|----------------|------------------------------|-------|-----------|--------------------------|-----------|
| 8 | | | | | TOLERANCE | | | | |
| 7 | | | | | UNLESS SPECIFIED | | | | |
| 6 | | | | | WITHIN 1.5mm : ±0.1mm | A | 2012-8-13 | 初版 | |
| 5 | SPRING | SUS | 1 | NATURAL | OVER 1.5mm : ±0.2mm | ISSUE | DATE | DESCRIPTIONS OF REVISION | |
| 4 | CAM STICK | SUS | 1 | NATURAL | TITLE : VERTICAL PUSH SWITCH | | | UNIT : mm | DRWG NO.: |
| 3 | CASE | PA66/BRASS STRIP | 1 | GREY/Ag PLATED | MODEL: | | | SCALE: 5:1 | DWN. |
| 2 | COVER | PA66 | 1 | BLACK | 东莞市高迪电子有限公司 | | | | 2012-8-13 |
| 1 | KNOB | PA66/PBS C5210R-EH | 1 | WHITE/Ag CLAD | | | | CHK'D | |
| NO. | PARTS | MATERIALS | Q'TY | | | | | APPD. | |