



SPECIFICATIONS

Rating	0.1A 12V DC
Insulation Resistance	50MΩ Min.
Dielectric Withstanding Voltage	AC 250 V(50Hz)1min
Contact Resistance	100mΩ Max.
Operating Life	50,000 cycles

P.C.B LAND PATTERN

E	TERMINAL	3	PHOSPHOR BRONZE	Ag plated
D	CONTACT	2	SUS	Ag plated
C	COVER	1	SUS	Ag plated
B	CASE	1	LCP	Black
A	Knob	1	PA46	Black
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	07/30/13			
CHECKED BY:	DATE	FINISH	MODLE	Multi Function SWITCH
Jacky Chen	07/30/13			
APPROVED BY:	DATE	SCALE	DWG NO.	K03-S246
Tony Kao	07/30/13	1 : 1		
		SHEET NO.	PART NO.	K03-S246
		1 of 1		
				SIZE A4
				VER R1

1	更新材質	Jack	073013
ITEM NO.	DESCRIPTION	DRAWN	DATE